## **DISTANCE MEASURING DEVICE**

Patent number: ,

JP10096778 1998-04-14

Publication date:

ADACHI TADASHI

Inventor: Applicant:

KUBOTA KK

Classification:

- international:

A01B69/00: G01S17/08: A01B69/00: G01S17/00:

(IPC1-7): G01S17/08; A01B69/00

- european:

Application number: JP19960251073 19960924 Priority number(s): JP19960251073 19960924

Report a data error here

## Abstract of JP10096778

PROBLEM TO BE SOLVED: To improve distance measuring accuracy by making the most of respective characteristics of absolute distance information found from measuring information of a timer means by projecting a pulselike beam of light from a first distance measuring light source and distance information found by detecting a phase difference by a phase difference detecting means by applying a beam of light modulated from a second distance measuring light source, and joining them. SOLUTION: A laser position measuring device 40 is constituted so as to make common use of a single light emitting device 60 for a function as a first distance measuring light source FL to project a pulse-like beam of light toward a distance measuring object and a function as a second distance measuring light source SL to project a beam of light modulated by a reference signal of a preset period toward the distance measuring object. An operation device 70 finds absolute distance information from counting time of a timer 69. A phase difference detecting means FD finds a phase difference between a sine wave of a first oscillator 66 and a sine wave signal contained in a detecting signal of a light receiving element 62 from counting time of a timer 74. The operation device 70 finds a distance up to a distance measuring object from the absolute distance information by converting it into a distance corresponding to a phase difference.

